

3x1 Multi-Mode Pump Combiner

Features

High Transfer Efficiency
Air-Clad Technology for Robust Power Delivery
Stable and Reliable
Custom Configurations Available

Applications

High Power Fiber Laser
Fiber Amplifier

Specifications

Parameters	Value
Port Configuration	3x1
Pump Wavelength	800~1000nm
Pump Input Fiber	X/125 or 200/220
output Fiber	Y/125 or 200/220
Pump Efficiency	>95%
Total Handling Power	300W
Package Dimension	D1,D2,D3,D4
Operating Temperature	-5~+70
Storage Temperature	-40~+85

Ordering Information












MPC-111-222-333-44-56-777

111	- Port Configuration:	031=3x1
222	-Fiber Type for Input:	019=Nufern LMA-GDF-10/125-M, 021=Nufern LMA-GDF-20/130-M 031=Nufern LMA-GDF-30/250-M, 044=Nufern LMA-GDF-20/400-M 015=Nufern PM1060L-FA, 020=Nufern PLMA-GDF-20/130 030=Nufern PLMA-GDF-30/250-M, 035=Nufern PLMA-GDF-20/400-M
333	- Fiber Type for Output:	019=Nufern LMA-GDF-10/125-M, 021=Nufern LMA-GDF-20/130-M 031=Nufern LMA-GDF-30/250-M, 044=Nufern LMA-GDF-20/400-M 015=Nufern PM1060L-FA, 020=Nufern PLMA-GDF-20/130 030=Nufern PLMA-GDF-30/250-M, 035=Nufern PLMA-GDF-20/400-M
44	- Package Dimension:	D1,D2,D3,D4,D5,D6,D7, S= Specified
5	-Pigtail Type:	0=250um bare fiber, 1=900um loose tube
6	-Fiber Type:	0=0.8m, 1=1.0m
777	-Handling Power/Per Pump:	005=5W, 010=10W, 100=100W, 200=200W

Note:1.Other package dimension and optical performance can meet customer design;

2.Pleased to contact us if you need more fiber selection

Package Dimensions:

Type	Dimension (Mounting)	Schematic	Schematic	Note
D1	Φ4x60mm			Low power with glass tube Dissipated power<5W
D2	50x5x5mm			Low power with glass tube Dissipated power<5W
D3	70x12x8mm (54x7.0mm)			Low power with glass tube Dissipated power<10W
D4	75x12x8mm (54x7.0mm)			Mid power package, up to 1200W Dissipated power<50W
D5	80x14x10mm (54x8.4mm)			Mid power package up to 2500W Dissipated power<70W
D6	105x15x8mm (40x11mm)			Mid power package up to 1500W Dissipated power<60W
D7	100x28x12.6mm (66x23mm)			High power package up to 5000W Dissipated power<200W