

Typical Device Performance

LIEKKI™ Passive Fiber	Core	±	Cladding	±	Coating	±	NA	±	Clad ding NA	Birefrin- gence	Proof Test	Matching Active Fiber
Passive-6/125*	6.0	0.5	125	2	245	15	0.15	0.01			100	Yb1200-6/125DC
M05-A-055-A Passive-6/125DC*	6.0	0.5	125	2	245	15	0.15	0.01	0.46		100	Yb1200-6/125DC
Passive-6/125DC-PM*	6.0	0.5	125	2	245	15	0.15	0.01	0.46	2.0E-04	100	Yb1200-6/125DC-PM
Passive-10/125	10	1	125	2	245	15	0.08	0.01			100	Yb1200-10/125D C
M05-A-037-A Passive-10/125DC	10	1	125	2	245	15	0.08	0.01	0.46		100	Yb1200-10/125D C
Passive-10/125-PM	10	1	125	2	245	15	0.08	0.01				Yb1200-10/125D C-PM
M05-A-036-A Passive-10/125DC-PM	10	1	125	2	245	15	0.08	0.01	0.46	1.4E-04	100	Yb1200-10/125D C-PM
Passive-12/125	12.5	1	125	2	245	15	0.08	0.01			100	Yb1200-12/125D C
M05-A-054-A Passive-12/125DC	12.5	1	125	2	245	15	0.08	0.01	0.46		100	Yb1200-12/125D C
M05-A-053-A Passive-12/125DC-PM	12.5	1	125	2	245	15	0.08	0.01	0.46	1.4E-03	100	Yb1200-12/125D C-PM
Passive-12/125-PM	12.5	1	125	2	245	15	0.08	0.01		1.4E-03	100	Yb1200-12/125D C-PM
Passive-20/125	20	2	125	2	245	15	0.08	0.01			100	Yb1200-20/125D C
Passive-20/125DC	20	2	125	2	245	15	0.08	0.01	0.46		100	Yb1200-20/125D C
Passive-20/125-PM	20	2	125	2	245	15	0.08	0.01		8.0E-05	100	Yb1200-20/125D C-PM
Passive-20/125DC-PM	20	2	125	2	245	15	0.08	0.01	0.46	8.0E-05	100	Yb1200-20/125D C-PM
Passive-20/400	20	2	400	8	520	15	0.07	0.01			50	Yb1200-20/400D C
Passive-20/400DC	20	2	400	8	520	15	0.07	0.01	0.46		50	Yb1200-20/400D C
Passive-20/400-PM	20	2	400	8	520	15	0.07	0.01		1.6E-04	50	Yb1200-20/400D C-PM

Proven Performance

LIEKKI™ Passive Fiber	Core	±	Cladding	±	Coating	±	NA	±	Clad ding NA	Birefrin- gence	Proof Test	Matching Active Fiber
Passive-20/400DC-PM	20	2	400	8	520	15	0.07	0.01	0.46	1.6E-04	50	Yb1200-20/400D C-PM
Passive-20/400/460DC, All-glass	20	2	400	8	580	15	0.07	0.01	0.22		50	
Passive-25/250	25	2.5	250	5	350	15	0.07	0.01			100	Yb1200-25/250D C
Passive-25/250-PM	25	2.5	250	5	350	15	0.07	0.01		1.6E-04	100	Yb1200-25/250D C-PM
MOS-A-028-A Passive-25/250DC	25	2.5	250	5	350	15	0.07	0.01	0.46		100	Yb1200-25/250D C
Passive-25/250DC-PM	25	2.5	250	5	350	15	0.07	0.01	0.46	1.6E-04	100	Yb1200-25/250D C-PM
Passive-30/250			250	5	350	15	0.07	0.01			100	Yb1200-30/250D C
Passive-30/250-PM	30	3	250	5	350	15	0.07	0.01		1.6E-04	100	Yb1200-25/250D C-PM
MOS-A-029-A Passive-30/250DC	30	3	250	5	350	15	0.07	0.01	0.46		100	Yb1200-30/250D C
Passive-30/250DC-PM	30	3	250	5	350	15	0.07	0.01	0.46	1.6E-04	100	Yb1200-30/250D C-PM
Passive-125DC			125	3	250	15	0.46		0.46		100	
Passive-250DC			250	5	350	15	0.46		0.46		100	
Passive-400DC			400	8	520	15	0.46		0.46		50	
Passive-200/220DC, 0.22NA	200	4	220	5	350	15	0.23	0.01	0.46		100	

* Core diameter specification refers to the mode field diameter.

2023.01.30
受控文件

公司
日期

Proven Performance

sales@nlight.net • www.nlight.net