

HI 1060	
Key Optical Specifications	
Operating Wavelength (nm)	> 980
Maximum Attenuation (dB/km)	2.1 @ 980 nm 1.5 @ 1060 nm
Cutoff Wavelength (nm)	920 ± 50
Mode-field Diameter (μm)	5.9 ± 0.3 @ 980 nm 6.2 ± 0.3 @ 1060 nm
Key Geometric, Mechanical and Environmental Specifications	
Cladding Outside Diameter (μm)	125 ± 0.5
Coating Outside Diameter (μm)	245 ± 10
Core-to-Cladding Offset (μm)	≤ 0.3
Standard Lengths	500 m, 1 km, 2 km, 5 km, 10 km*
Proof Test (kpsi)	100 or 200
Operating Temperature (°C)	-60 to 85
*10 km lengths only available for HI 1060	
Performance Characterizations**	
Nominal Delta (%)	0.48
Numerical Aperture	0.14
Refractive Index Value – Core	1.464 @ 651 nm
Dispersion (ps/nm/km)	-53 @ 980 nm -38 @ 1060 nm
Bendloss (@ 20 mm O.D.; 1150 nm) (dB/turn)	≤ 0.01
Core Diameter (μm)	5.3
** Values in this table are nominal or calculated values	
M05-A-004-A	

Typical Splice Loss

	HI 1060	RC PANDA PM 980	SMF-28e+ Fiber	RC SMF Fiber
Wavelength (nm)	1550	980	1550	1550
RC HI 1060 (dB)	0.04	0.07	0.16	0.08



For more information about Corning's leadership in Specialty Fiber technology visit our website at www.corning.com/specialtyfiber
To obtain additional technical information, an engineering sample or to place an order for this product, please contact us at:

Corning Incorporated Tel: +1-607-974-9974
Fax: +1-607-974-4122
E-mail: specialtyfiber@corning.com

© 2010 Corning Incorporated



M0100008
Issued: March 2010
Supersedes: August 2003

Corning® HI 1060 & RC HI 1060

Specialty Optical Fibers

High Index / Bend Insensitive

CORNING



*Industry standard
for 980 pump
pigtails for high
performance
components and
small footprint
assemblies*

*Manufactured with Corning's
patented Outside Vapor
Deposition (OVD) process,
Corning® HI 1060 Specialty
Fiber offers world-class
durability and reliability. When
used as component pigtails,
this fiber allows for efficient
fiber coupling within photonic
products.*

Applications:

HI 1060

- Photonic products and fused fiber couplers
- Component fiber for EDFAs, couplers, and other DWDM components
- Laser diode pigtails
- Gratings

RC HI 1060

- Component fiber for EDFAs, couplers, and other DWDM components
- Pigtails for pump lasers

Features:

HI 1060 and RC HI 1060

- Outstanding consistency and uniformity using Corning's patented Outside Vapor Deposition (OVD) process
- Dual acrylate coating system provides excellent protection from microbend-induced attenuation and superior mechanical robustness
- Excellent geometry control
- High core index of refraction
- Efficient coupling
- High numerical aperture
- RC HI 1060 offers 80 μm diameter for miniature packaging

