

## 1064nm 300mW Non-PM Isolator (Faraday Based)

### Features

- Low Insertion Loss
- High Return Loss
- High Isolation
- High Stability & Reliability

### Applications

- MOPA Fiber Laser
- Test Instruments
- Fiber Laser
- Research

### Specifications

Parameter	Unit	Value	
Type	-	Polarization Insensitive	
Stage	-	Single	Dual
Center Wavelength	nm	1064	
Operating Wavelength Range	nm	±5	
Typ. Peak Isolation at 23°C	dB	35	52
Min. Isolation at 23°C	dB	28	45
Typ. Insertion Loss at 23°C	dB	1.5	2.4
Max. Insertion Loss at 23°C	dB	1.8	3.2
Min. Return Loss at 23°C (input/output)	dB	50/50	
Max. Polarization Dependent Loss at 23°C	dB	0.15	
Max. Optical Power (CW)	mW	300	
Max. Tensile Load	N	5	
Fiber Type	-	Single-mode fiber	
Operating Temperature	°C	-5~+50	
Storage Temperature	°C	-40~+85	

\*With connectors, IL is 0.3dB higher and RL is 5dB lower.

### Package Dimensions



### Ordering Information

PIIS-①①①①-②③-④④④-⑤⑥-⑦-⑧⑧

①①①① - Wavelength:	1064=1064nm, SSSS=Specified
② - Core Type:	S=Single-core stage, D=Dual-core stage
③ - Working Axis:	N=Non-PM
④④④ - Fiber Type:	004=Hi1060, SSS=Specified
⑤ - Package:	0=φ5.5x35mm
⑥ - Dimensions:	0=bare fiber, 1=900μm loose tube, S=Specified
⑦ - Pigtail Type:	0.8=0.8m, 1.0=1m, S=Specified
⑧⑧ - Connector Type:	0=FC/UPC, 1=FC/APC, 2=SC/UPC, 3=SC/APC, N=None, S=Specified